







	لیست قیمت محصولات هایک ویژن مهر 1399	شرکت هوشمندافزار آسیا 5- 02634200921	دوربین مدار بسته TURBO HD	
قیمت (ریال)	مشخصات فنی	تصویر	مدل کالا	ردیف
6,160,000	1 Mp 720P resolution Smart IR Up to 20m IR distance IP66 weatherproof		DS-2CE16C0T-IRP	1
7,490,000	2 mp Smart IR Up to 20m IR distance IP66 weatherproof Metal		DS-2CE16D0T-IF	2
20,210,000	2 megapixel highperformance CMOS Analog HD output, up to 1080presolution Day / Nightswitch Smart IR Up to 40m IR distance Switchable TVI/AHD/CVI/CVBS IP66		DS-2CE16D0T-VFIR3F	
15,410,000	5MP high performance COMS 2560 × 1944 resolution 20fps 4 MP@25fps 2.8 mm, 3.6 mm, 6 mm fixed lens EXIR2.0, smart IR, up to 20 m IR Distance OSD menu DWDR 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67 Up the coax (HIKVISION-C) Material: Front cover: Metal Main body: Plastic		DS-2CE16H0T-IT1F	3
16,630,000	5MP high performance OMS 2560 × 1944 resolution 20fps 4 MP@25fps 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens EXIR2.0, smart IR, up to 40 m IR distance OSD menu, 2D DNR, DWDR 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67 Up the coax (HIKVISION-C)		DS-2CE16H0T-IT3F	4
28,690,000	5MP high performance COMS 2560 × 1944 resolution 20fps 4 MP@25fps 2.7mm to 13.5 mm motorized vari-focal lens EXIR2.0, smart IR, up to 40 m IR distance OSD menu, 2D DNR, DWDR 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67 Up the coax (HIKVISION-C)		DS-2CE16H0T-IT3ZF	5

14,130,000	<p>5MP high performance COMS 2560 × 1944 resolution 20fps 4 MP@25fps 2.8 mm, 3.6 mm, 6 mm fixed lens EXIR2.0, smart IR, up to 20 m IR distance OSD menu, 2D DNR, DWDR 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67 Up the coax (HIKVISION-C)</p>		DS-2CE16H0T-ITF	6
17,460,000	<p>5MP high-performance CMOS 2560× 1440@30fps, 2560× 1440@25fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens EXIR2.0, smart IR, up to 20m IR distance OSD menu DWDR IP67 PoC.af POC Up the coax (HIKVISION-C)</p>		DS-2CE16H1T-ITE	7
19,960,000	<p>5MP high-performance CMOS 2560× 1440@30fps, 2560× 1440@25fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens EXIR2.0, smart IR, up to 20 m IR distance OSD menu, DNR, DWDR IP67 PoC.af POC Up the coax (HIKVISION-C)</p>		DS-2CE16H1T-IT1E	8
21,620,000	<p>5MP high-performance CMOS 2560× 1440@30fps, 2560× 1440@25fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens EXIR2.0, smart IR, up to 40 m IR distance OSD menu, DNR, DWDR IP67 PoC.af POC Up the coax (HIKVISION-C)</p>		DS-2CE16H1T-IT3E	9
23,280,000	<p>5MP high-performance CMOS 2560 × 1944 resolution 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens EXIR2.0, smart IR, up to 80 m IR distance OSD menu, DNR, DWDR IP67 PoC.at POC Up the coax (HIKVISION-C)</p>		DS-2CE16H1T-IT5E	10
تماس حاصل فرماید	<p>5MP high-performance CMOS 2560× 1440@30fps, 2560× 1440@25fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens EXIR2.0, smart IR, up to 40 m IR distance OSD menu, DNR, DWDR IP67 PoC.af POC Up the coax (HIKVISION-C)</p>		DS-2CE56H1T-ITME	11
19,960,000	<p>5MP high-performance CMOS 2560× 1440@30fps, 2560× 1440@25fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens EXIR2.0, smart IR, up to 20 m IR distance OSD menu, DNR, DWDR IP67 PoC.af POC Up the coax (HIKVISION-C)</p>		DS-2CE56H1T-IT1E	12

<p>21,620,000</p>	<p>5MP high-performance CMOS 2560x 1440@30fps, 2560x 1440@25fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens EXIR2.0, smart IR, up to 40 m IR distance OSD menu, DNR, DWDR IP67 PoC.af POC Up the coax (HIKVISION-C)</p>		<p>DS-2CE56H1T-IT3E</p>	<p>13</p>
<p>34,920,000</p>	<p>5 MP high-performance CMOS 2560 x 1944 resolution 2.8 mm to 12 mm motorized vari-focal lens EXIR2.0, smart IR, up to 40 m IR distance OSD menu, DNR, DWDR IP67 PoC.at POC Up the coax (HIKVISION-C)</p>		<p>DS-2CE56H1T-IT3ZE</p>	<p>14</p>



<p>49,890,000</p>	<p>8.29MP high performance CMOS Ultra-low light 3840 x2160 resolution 12.5fps 5 MP@20fps, 4 MP@25fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens 120 dB true WDR, 3D DNR EXIR2.0, smart IR, up to 60 m IR distance IP67 Up the coax (HIKVISION-C)</p>		<p>DS-2CE18U8T-IT3</p>	<p>15</p>
<p>6,070,000</p>	<p>2 megapixel high performance CMOS PAL: 1080p@25fps, NTSC: 1080p@30fps Smart IR Up to 20 m IR distance Switchable TVI/AHD/CVI/CVBS</p>		<p>DS-2CE56D0T-IPF</p>	<p>16</p>
<p>20,210,000</p>	<p>2 megapixel high performance CMOS 1080p@25fps - 1080p@30fps Lens : 2.8-12 mm Smart IR Up to 40m IR distance Switchable TVI/AHD/CVI/CVBS IP66</p>		<p>DS-2CE56D0T-VFIR3F</p>	<p>17</p>
<p>17,460,000</p>	<p>2MP high performance CMOS Ultra-Low Light 1920 x1080 resolution PAL: 1080p@25fps, NTSC: 1080p@30fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens 120 dB true WDR 3D DNR EXIR2.0, Smart IR, up to 20 m IR distance PoC.af (POC) IP67 Up the Coax (HIKVISION-C)</p>		<p>DS-2CE56D8T-IT1E</p>	<p>18</p>
<p>16,630,000</p>	<p>2 MP high performance COMS Ultra-Low Light 1920x1080 resolution PAL: 1080p@25fps, NTSC: 1080p@30fps 2.8 mm, 3.6 mm, 6 mm fixed focal lens 120 dB true WDR, 3D DNR EXIR2.0, Smart IR, up to 20m IR distance PoC.af (POC) IP67 Up the Coax (HIKVISION-C)</p>		<p>DS-2CE56D8T-ITME</p>	<p>19</p>

<p>33,260,000</p>	<p>3 Mp high-performance CMOS 2.8mm-12mm motorized vari-focal lens Smart IR WDR, up to 120Db EXIR technology, up to 40m IR distance IP66 weatherproof Up the Coax(HIKVISION-C)</p>		<p>DS-2CE56F7T-IT3Z</p>	<p>20</p>
<p>15,800,000</p>	<p>5 MP high performance COMS 2560 x 1944 resolution PAL: 5MP@20fps, 4MP@25fps NTSC: 5MP@20fps, 4MP@30fps 2.8 mm, 3.6 mm, 6 mm fixed lens EXIR2.0, smartIR, up to 20 m IR distance OSD menu, 2D DNR, DWDR 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67 Up the coax (HIKVISION-C)</p>		<p>DS-2CE56H0T-IT1F</p>	<p>21</p>
<p>16,250,000</p>	<p>5 MP high performance COMS 2560 x 1944 resolution PAL: 5MP@20fps, 4MP@25fps NTSC: 5MP@20fps, 4MP@30fps 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens EXIR2.0, smart IR, up to 40 m IR distance OSD menu, 2D DNR, DWDR 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67 Up the coax (HIKVISION-C)</p>		<p>DS-2CE56H0T-IT3F</p>	<p>22</p>

<p>28,270,000</p>	<p>5 MP high performance COMS 2560 x 1944 resolution 2.7mm to 13.5 mm motorized vari-focal lens EXIR2.0, smart IR, up to 40 m IR distance OSD menu, 2D DNR, DWDR 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67 Up the coax (HIKVISION-C)</p>		<p>DS-2CE56H0T-IT3ZF</p>	<p>23</p>
<p>19,960,000</p>	<p>5MP high-performance CMOS 2560 x 1944 resolution PAL: 5 MP@20fps, 4 MP@25fps NTSC: 5 MP@20fps, 4 MP@30fps, 2.8 mm, 3.6 mm, 6 mm fixed focal lens EXIR2.0, smart IR, up to 20 m IR distance OSD menu, DNR, DWDR IP67 PoC.af (POC) Up the coax (HIKVISION-C)</p>		<p>DS-2CE56H1T-IT1E</p>	<p>24</p>
<p>47,390,000</p>	<p>8.29MP high performance CMOS Ultra-low light 3840 x 2160 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens 120 dB true WDR, 3D DNR EXIR2.0, smart IR, up to 60 m IR distance IP67 Up the coax (HIKVISION-C)</p>		<p>DS-2CE78U8T-IT3</p>	<p>25</p>




<p>14,550,000</p>	<p>5 MP PIR Fixed Mini Bullet Camera</p> <p>PIR detection and strobe light alarm to warn off intruders in real time</p> <p>EXIR 2.0: advanced infrared technology with 20 m IR distance</p> <p>Water and dust resistant (IP67)</p>		<p>DS-2CE11H0T-PIRL</p>	<p>26</p>
<p>15,800,000</p>	<p>5 MP PIR Fixed Bullet Camera</p> <p>PIR detection and strobe light alarm to warn off intruders in real time</p> <p>EXIR 2.0: advanced infrared technology with 20 m IR distance</p> <p>Water and dust resistant (IP67)</p>		<p>DS-2CE12H0T-PIRL</p>	<p>27</p>
<p>9,150,000</p>	<p>2.0 megapixel high-performance CMOS</p> <p>HD analogue output, up to 1080p resolution</p> <p>2.8 mm, 3.6 mm, 6 mm fixed focal lens</p> <p>True Day/Night</p> <p>Up to 20 m IR distance</p> <p>IP66</p>		<p>DS-2CE16D0T-IR</p>	<p>28</p>
<p>10,810,000</p>	<p>2.0 megapixel high-performance CMOS</p> <p>HD analogue output, up to 1080p resolution</p> <p>2.8 mm, 3.6 mm, 6 mm fixed focal lens</p> <p>True Day/Night</p> <p>Up to 20 m IR distance</p> <p>IP66</p> <p>PoC.af</p> <p>Up the Coax (HIKVISION-C)</p>		<p>DS-2CE16D0T-IRE</p>	<p>29</p>

<p>10,210,000</p>	<p>2 MP Fixed Mini Bullet Camera</p> <p>Smart IR: up to 20 m IR distance</p> <p>Water and dust resistant (IP66)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>		<p>DS-2CE16D0T-IRF</p>	<p>30</p>
<p>12,310,000</p>	<p>2 MP Fixed Bullet Camera</p> <p>EXIR 2.0: advanced infrared technology with 40 m IR distance</p> <p>Water and dust resistant (IP66)</p>		<p>DS-2CE16D0T-IT3</p>	<p>31</p>
<p>11,720,000</p>	<p>2 MP Audio Fixed Mini Bullet Camera</p> <p>Enhancing safety with discreet and economical built-in microphone</p> <p>Transmits audio over the coaxial cable</p> <p>EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>		<p>DS-2CE16D0T-ITFS</p>	<p>32</p>
<p>12,890,000</p>	<p>2 MP Ultra Low Light Fixed Mini Bullet Camera</p> <p>Strong night performance, capturing images in ultra-low light down to 0.005 lux</p> <p>Clear imaging even against strong back lighting due to 120 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images</p> <p>Smart IR: up to 30 m IR distance</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>		<p>DS-2CE16D3T-I3F</p>	<p>33</p>




<p>19,760,000</p>	<p>2 MP Ultra Low Light PoC Fixed Bullet Camera</p> <p>Strong night performance, capturing images in ultra-low light down to 0.003 lux</p> <p>Clear imaging even against strong back lighting due to 130 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images</p> <p>EXIR 2.0: advanced infrared technology with 60 m IR distance</p> <p>Water and dust resistant (IP67)</p>		<p>DS-2CE16D8T-IT3E</p>	<p>34</p>
<p>34,090,000</p>	<p>2MP high performance CMOS</p> <p>Adopts HD-TVI technology</p> <p>Ultra low light</p> <p>TVI test monitor port</p> <p>2.8 - 12mm motorized varifocal lens</p> <p>True day/night</p> <p>OSD menu</p> <p>Smart IR</p>		<p>DS-2CE16D8T-IT3ZE</p>	<p>35</p>

	<p>EXIR2.0 technology</p> <p>Up to 40m IR distance</p> <p>IP67 weatherproof</p>			
<p>16,630,000</p>	<p>2MP Ultra Low Light POC Fixed Bullet Camera</p> <p>Strong night performance, capturing images in ultra-low light down to 0.003 lux</p> <p>Clear imaging even against strong back lighting due to 130 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images</p> <p>EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67)</p>		<p>DS-2CE16D8T-ITE</p>	<p>36</p>
<p>33,260,000</p>	<p>3Megapixel high-performance CMOS</p> <p>Analog HD output, up to 3MP resolution</p> <p>2.8-12mm motorized vari-focal lens</p> <p>True Day/Night</p> <p>OSD menu, DNR, Smart IR</p> <p>True WDR, up to 120dB</p> <p>EXIR technology, up to 40m IR distance</p> <p>IP66 weatherproof</p>		<p>DS-2CE16F7T-IT3Z</p>	<p>37</p>


<p>17,880,000</p>	<p>5 MP Fixed Bullet Camera</p> <p>EXIR 2.0: advanced infrared technology with 80 m IR distance</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>		<p>DS-2CE16H0T-IT5F</p>	<p>38</p>
<p>تماس حاصل فرمایید</p>	<p>8.29MP high performance COMS</p> <p>Ultra-low light</p> <p>3840×2160 resolution</p> <p>Auto focus, 2.8 mm to 12 mm motorized varifocal lens</p> <p>120 dB true WDR, 3D DNR</p> <p>EXIR 2.0, smart IR, up to 80 m IR distance</p> <p>Dual video output: TVI/CVBS</p> <p>Dual voltage input: 12 VDC ±25%/24VAC±25%</p> <p>IP67</p>		<p>DS-2CE19U8TA-IT3Z</p>	<p>39</p>
<p>5,410,000</p>	<p>1 MP Fixed Indoor Turret Camera</p> <p>HD 720p turret camera</p> <p>Smart IR: up to 20 m IR distance</p>		<p>DS-2CE56C0T-IRP</p>	<p>40</p>
<p>5,820,000</p>	<p>1 MP Fixed Indoor Turret Camera</p> <p>HD 720p turret camera</p> <p>Smart IR: up to 20 m IR distance</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>		<p>DS-2CE56C0T-IRPF</p>	<p>41</p>
<p>8,730,000</p>	<p>2 MP Fixed Turret Camera</p> <p>Smart IR: up to 20 m IR distance</p> <p>Water and dust resistant (IP66)</p>		<p>DS-2CE56D0T-IR</p>	<p>42</p>
<p>9,150,000</p>	<p>2 MP Fixed Turret Camera</p> <p>Smart IR: up to 20 m IR distance</p> <p>Water and dust resistant (IP66)</p>		<p>DS-2CE56D0T-IRM</p>	<p>43</p>

<p>8,980,000</p>	<p>2 MP Fixed Turret Camera</p> <p>Smart IR: up to 20 m IR distance</p> <p>Water and dust resistant (IP66)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>		<p>DS-2CE56D0T-IRMF</p>	<p>44</p>
<p>11,730,000</p>	<p>2 MP Fixed Turret Camera</p> <p>EXIR 2.0: advanced infrared technology with 40 m IR distance</p> <p>Water and dust resistant (IP66)</p>		<p>DS-2CE56D0T-IT3</p>	<p>45</p>
<p>13,720,000</p>	<p>2 MP PoC Fixed Turret Camera</p> <p>EXIR 2.0: advanced infrared technology with 40 m IR distance</p> <p>Water and dust resistant (IP66)</p> <p>Transmits both HD video and power over the same coaxial cable</p>		<p>DS-2CE56D0T-IT3E</p>	<p>46</p>

<p>12,940,000</p>	<p>3 Megapixel high-performance CMOS</p> <p>Analog HD output, up to 3MP resolution</p> <p>True Day/Night. OSD menu, DNR, Smart IR.</p> <p>EXIR technology, up to 40m IR distance. IP66 weatherproof</p> <p>Can only be used on DS-7200HUHI-F1/N Series DVRs at 3MP</p> <p>1 x DS-2CE56F1T-IT3 3.6MM</p>		<p>DS-2CE56F1T-IT3</p>	<p>47</p>
<p>12,890,000</p>	<p>5MP high performance CMOS</p> <p>Adopts HD-TVI technology</p> <p>2.8mm fixed lens</p> <p>True day/night</p> <p>OSD menu</p> <p>4 in 1 video output (TVI/AHD/CVI/CVBS)</p> <p>Smart IR</p> <p>EXIR2.0 technology</p> <p>Up to 20m IR distance</p>		<p>DS-2CE56H0T-ITMF</p>	<p>48</p>
<p>تماس حاصل فرمایید</p>	<p>5 MP high performance COMS</p> <p>Ultra-low light</p> <p>2560 × 1944 resolution</p> <p>2.8 mm, 3.6 mm, 6 mm fixed focal lens</p> <p>EXIR2.0, smart IR, up to 20 m IR distance</p> <p>OSD menu, DNR, DWDR</p> <p>IP67, IK10</p> <p>PoC.af</p>		<p>DS-2CE56H5TVP-ITE</p>	<p>49</p>





تماس حاصل فرمایید	<p>2MP high performance CMOS 4 in 1, can be used as TVI, CVI, AHD or Analogue camera Full time colour Fixed lens True day/night OSD menu Up to 20m white light distance IP67 weatherproof</p>		DS-2CE72DFT-F	50
10,590,000	<p>2 MP Fixed Turret Camera EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>		DS-2CE76D0T-ITMF	51
11,720,000	<p>1080P HD Video output Switchable TVI/AHD/CVI/CVBS 2.8mm fixed lens True day/night Up to 30m IR distance IP67 weatherproof Digital wide dynamic range</p>		DS-2CE76D0T-ITMFS	52

14,360,000	<p>5MP high performance CMOS 4 in 1, can be used as TVI, CVI, AHD or Analogue camera 2.8mm fixed lens True day/night OSD menu Smart IR Up to 30m IR distance IP67 weatherproof</p>		DS-2CE76H0T-ITMFS	53
------------	--	--	-------------------	----

	لیست قیمت محصولات هایک ویژن مهر 1399	شرکت هوشمندافزار آسیا 5- 02634200921	DVR	
---	---	---	-----	--





قیمت	مشخصات فنی	تصویر	مدل کالا	ردیف
36,840,000	<p>8-ch 1080p Mini 1U H.265 DVR 8 channels and 1 HDD mini size DVR Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/ AHD/CVI/CVBS/IP) Up to 12 network cameras can be connected</p>		DS-7108HQHI-K1	54

<p>58,720,000</p>	<p>H.265 Pro+/H.265 Pro/H.265 video compression</p> <p>1 HDD Up to 6TB capacity</p> <p>HDTVI input 4 MP lite</p> <p>The 3 MP signal input is only available for channel 1/2/3/4 of DS-7116HQHI-K1.</p> <p>AHD input : 4 MP, 1080p25, 1080p30, 720p25, 720p30</p> <p>HDCVI input : 4 MP, 1080p25, 1080p30, 720p25, 720p30</p> <p>CVBS input : Support</p>		<p>DS-7116HQHI-K1</p>	<p>55</p>
<p>26,620,000</p>	<p>H.265 Pro+/H.265 Pro/H.265 video compression</p> <p>Up to 6-ch IP camera inputs(up to 6 MP)</p> <p>1 HDD Up to 10TB capacity</p> <p>HDTVI input : 4MP lite *: The 3 MP signal input is only available for channel 1 of DS-7204HQHI-K1</p> <p>AHD input : 4 MP</p> <p>HDCVI input : 4 MP</p> <p>CVBS input : PAL/NTSC</p> <p>CVBS output : support</p>		<p>DS-7204HQHI-K1</p>	<p>56</p>
<p>49,890,000</p>	<p>H.265 Pro+/H.265 Pro/H.265 video compression</p> <p>Up to 4-ch IP camera inputs (up to 8 PM)</p> <p>1 HDD Up to 10TB capacity per HDD</p> <p>HDTVI input : 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p25, 720p30</p> <p>AHD input : 5 MP, 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30</p> <p>HDCVI input : 5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30</p> <p>CVBS input : PAL/NTSC</p> <p>CVBS output : support</p> <p>Audio input : 4-ch</p>		<p>DS-7204HTHI-K1</p>	<p>57</p>
<p>42,840,000</p>	<p>Connectable to HD-TVI, AHD, IP, CVI & analogue cameras</p> <p>Audio via coaxial cable with compatible cameras (AoC)</p> <p>Long distance transmission over twisted pair cable & coax cable</p> <p>H.265+ compression improves encoding efficiency by up to 50% & reduces data storage costs</p> <p>12fps recording at 5MP, 15fps recording on 4MP, 18fps recording on 3MP</p>		<p>DS-7204HUHI-K1</p>	<p>58</p>

<p>47,050,000</p>	<p>H.265 Pro+/H.265 Pro/H.265 video compression POC power over coax Up to 4-ch IP camera inputs (up to 8 PM) 1 HDD Up to 10TB capacity per HDD HDTV input : 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, AHD input : 5 MP, 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30 HDCVI input : 5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30 CVBS input : PAL/NTSC CVBS output : support Audio input : 4-ch</p>		<p>DS-7204HUHI-K1/P</p>	<p>59</p>
<p>31,430,000</p>	<p>Support H.264+/H.264 video compression Up to 5-ch 960p IP camera input Max.1200 m for 720p HDTV signal When 1080p lite mode not enabled: 720p/WD1/4CIF/VGA/CIF When 1080p lite mode enabled: 1080p lite/HD 720p lite Audio input : 1-ch</p>		<p>DS-7208HGHI-F1</p>	<p>60</p>
<p>40,140,000</p>	<p>H.265 Pro+/H.265 Pro/H.265 video compression Up to 12-ch IP camera inputs(up to 6 MP) 1 HDD Up to 10TB capacity per HDD When 1080p lite mode is not enabled: 4 MP lite/3 P/1080p/720p When 1080p Lite mode is enabled: 4 MP lite/3 MP/1080p lite/720p lite IP video input : 8 ipc up to 8 mp</p>		<p>DS-7208HQHI-K1</p>	<p>61</p>
<p>38,020,000</p>	<p>HIKVision 4ch POC Turbo HD/AHD/Analog interface input 4ch video & 4ch audio input H.265/H.265+ 2 x USB 2.0 HDMI/VGA+BNC 1 SATA interface 5MP:12fps Alarm I/O: 4/1</p>		<p>DS-7208HQHI-K1/ECO</p>	<p>62</p>

<p>61,260,000</p>	<p>Connectable to HD-TVI, AHD, IP, CVI & analogue cameras Audio via coaxial cable with compatible cameras (AoC) Up to 4ch 8MP ONVIF conformant IP cameras input / 8ch with enhanced IP mode enabled Long distance transmission over twisted pair cable & coax cable H.265+ compression improves encoding efficiency by up to 50% & reduces data storage costs 8fps recording at 8MP, 12fps recording at 5MP, 15fps recording on 4MP, 18fps recording on 3MP</p>		<p>DS-7208HUHI-K1</p>	<p>63</p>
<p>96,990,000</p>	<p>H.265 Pro+/H.265 Pro/H.265 video compression Up to 8-ch IP camera inputs (up to 8 PM) 2 HDD Up to 10TB capacity per HDD HDTV input : 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, AHD input : 5 MP, 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30 HDCVI input : 5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30 CVBS input : PAL/NTSC CVBS output : support Audio input : 4-ch</p>		<p>DS-7208HTHI-K2</p>	<p>64</p>

<p>87,770,000</p>	<p>H.265 Pro+/H.265 Pro/H.265/H.264+ Video compression Encoding resolution : 8 MP@8fps/5 MP@12fps/4 MP@15fps/3 MP@18fps/1080p/720p IP video input : 8-ch Up to 8MP resolution PoC camera input : Support Hikvision PoC camera Audio input : 4-ch 2 HDD up to 10 TB per HDD</p>		<p>DS-7208HUHI-K2/P</p>	<p>65</p>
<p>38,830,000</p>	<p>Support H.265 Pro+/H.265 Pro/H.265 video compression Up to 18-ch IP camera input (up to 5 MP) 1 HDD Up to 10TB capacity per HDD HDTV input 1080p25, 1080p30, 720p25, 720p30 AHD input : 1080p25, 1080p30, 720p25, 720p30 HDCVI input : 1080p25, 1080p30, 720p25, 720p30 CVBS input PAL/NTSC</p>		<p>DS-7216HGHI-K1</p>	<p>66</p>

<p>68,860,000</p>	<p>H.265 Pro+/H.265 Pro/H.265 video compression Up to 24-ch IP camera inputs(up to 6 MP) 1 HDD Up to 10TB capacity per HDD When 1080p lite mode is not enabled: 4 MP lite/3 MP/1080p/720p When 1080p Lite mode is enabled: 4 MP lite/3 MP/1080p lite/720p lite IP video input : 8 ipc up to 8 mp Audio input : 1-ch</p>		<p>DS-7216HQHI-K1</p>	<p>67</p>
<p>65,460,000</p>	<p>Connectable to HD-TVI, AHD, IP, CVI & analogue cameras Audio via coaxial cable with compatible cameras (AoC) Up to 8ch 6MP ONVIF conformant IP cameras input / 24ch with enhanced IP mode enabled Long distance transmission over twisted pair cable & coax cable H.265+ compression improves encoding efficiency by up to 50% & reduces data storage costs 15fps recording 1080P</p>		<p>DS-7216HQHIK1/ECO</p>	<p>68</p>
<p>122,090,000</p>	<p>H.265 Pro+/H.265 Pro/H.265 video compression HDTV/HD/VI/CVI/CVBS/IP video input Up to 24-ch IP camera inputs(up to 6 MP) 2 HDD Up to 10TB capacity per HDD When 8 MPLite mode is not enabled: 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF When 8 MPLite mode is enabled:8MPLite/3MP/1080P/720P/WD1/4CIF/VGA/CIF IP video input : 16 ipc up to 8 mp Audio input : 4-ch</p>		<p>DS-7216HUHI-K2</p>	<p>69</p>
<p>132,650,000</p>	<p>Support H.265 Pro+/H.265 Pro/H.265 video compression Support HDTV/HD/VI/CVI/CVBS/IP video input 2 HDD Up to 10TB capacity per HDD When 1080p lite mode is not enabled: 4 MP lite/3MP/1080p/720p When 1080p Lite mode is enabled: 4 MP lite/3 MP/1080p lite/720p lite IP video input : 8-ch Up to 6MPresolution HDTV input : 4MP, 3MP, 1080p30,1080p25, 720p60, 720p50,720p30,720p25 *: The 3 MP signal input is only available for channel 1/2/3/4. AHD input : 4 MP, 1080p25, 1080p30, 720p25, 720p30 HDCVI input : 1080p25, 1080p30, 720p25, 720p30 CVBS input : PAL/NTSC CVBS output : 1-ch Audio input : 1-ch</p>		<p>DS-7232HQHI-K2</p>	<p>70</p>