





	لیست قیمت محصولات هایک ویژن مهر 1399	شرکت هوشمندافزار آسیا 5- 02634200921	دوربین مدار بسته تحت شبکه	
قیمت (ریال)	مشخصات فنی	تصویر	مدل کالا	ردیف
24,170,000	<p>2.0 MP IR Network Bullet Camera- 1/2.8"</p> <p>progressive scan CMOS</p> <p>3D DNR (Digital Noise Reduction)</p> <p>1920 × 1080@30fps</p> <p>Up to 30 m IR range</p> <p>2.8 mm/4 mm/6 mm fixed lens</p> <p>PoE (Power over Ethernet)</p> <p>H.265+, H.265, H.264+, H.264</p> <p>IP67 Dual stream</p> <p>Digital WDR (Wide Dynamic Range)</p>		DS-2CD1023G0-I	1
33,080,000	<p>4.0 MP IR Network Bullet Camera- 1/2.8"</p> <p>progressive scan CMOS</p> <p>3D DNR (Digital Noise Reduction)</p> <p>2560 × 1440@20fps</p> <p>Up to 30 m IR range</p> <p>2.8 mm/4 mm/6 mm fixed lens</p> <p>PoE (Power over Ethernet)</p> <p>H.265+, H.265, H.264+, H.264</p> <p>IP67 Dual stream</p> <p>Digital WDR (Wide Dynamic Range)</p>		DS-2CD1043G0-I	2
25,870,000	<p>2.0 MP IR Network Bullet Camera- 1/2.8"</p> <p>progressive scan CMOS</p> <p>3D DNR (Digital Noise Reduction)</p> <p>1920 × 1080@30fps</p> <p>Up to 30 m IR range</p> <p>2.8 mm/4 mm/6 mm fixed lens</p> <p>PoE (Power over Ethernet)</p> <p>H.265+, H.265, H.264+, H.264</p> <p>IP67, IK10 Dual stream</p> <p>Digital WDR (Wide Dynamic Range)</p>		DS-2CD1123G0-I	3



<p>34,770,000</p>	<p>4.0 MP IR Network Bullet Camera- 1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet) H.265+, H.265, H.264+, H.264 IP67, IK10 Dual stream Digital WDR (Wide Dynamic Range)</p>		<p>DS-2CD1143G0-I</p>	<p>4</p>
<p>55,120,000</p>	<p>2.0 MP IR Network Bullet Camera 1/2.8" progressive scan CMOS BLC/3D DNR/ROI 1920 × 1080@30fps Up to 30 m IR range 2.8 mm to 12 mm varifocal IP67 H.265+, H.265, H.264+, H.264 DigitalWDR Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD1623G0-IZ</p>	<p>5</p>
<p>59,360,000</p>	<p>4.0 MP IR Network Bullet Camera 1/2.8" progressive scan CMOS BLC/3D DNR/ROI 2560 × 1440@20fps Up to 30 m IR range 2.8 mm to 12 mm varifocal IP67 H.265+, H.265, H.264+, H.264 120 dB WDR Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD1643G0-I</p>	<p>6</p>
<p>53,430,000</p>	<p>4.0 MP IR Network Bullet Camera 1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range 2.8 mm to 12 mm manual vari-focal PoE (Power over Ethernet) IP67 H.265+, H.265, H.264+, H.264 Dual stream 120 dB WDR (Wide Dynamic Range)</p>		<p>DS-2CD1743G0-I</p>	<p>7</p>




<p>37,740,000</p>	<p>2 MP IR Fixed Bullet Network Camera 1/3" Progressive Scan CMOS 1920 × 1080@30fps 2.8/4/6/8 mm fixed lens H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI IP67 Builtin micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD2023G0-I</p>	<p>8</p>
<p>43,100,000</p>	<p>4 MP IR Fixed Bullet Network Camera 1/3" Progressive Scan CMOS 2688 × 1520@25fps 2.8/4/6/8 mm fixed lens H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI IP67 Builtin micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD2043G0-I</p>	<p>9</p>
<p>40,710,000</p>	<p>2 MP IR Fixed Dome Network Camera 1/2.8" Progressive Scan CMOS 1920 × 1080@30fps audio and alarm interface available 2.8/4/6/8mm fixed lens H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI/HLC IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD2123G0-IS</p>	<p>10</p>




<p>44,100,000</p>	<p>4 MP IR Fixed Dome Network Camera 1/2.8" Progressive Scan CMOS 2688 × 1520 @25fps audio and alarm interface available 2.8/4/6/8mm fixed lens H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses,and face detection BLC/3D DNR/ROI/HLC IP67, IK10 Built-in micro SD/SDHC/SDXC card slot,up to 128 GB</p>		<p>DS-2CD2143G0-IS</p>	<p>11</p>
<p>52,580,000</p>	<p>6 MP IR Fixed Dome Network Camera 1/2.8" Progressive Scan CMOS 3072 × 2048 @25fps audio and alarm interface available 2.8/4/6/8mm fixed lens H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses,and face detection BLC/3D DNR/ROI/HLC IP67, IK10 Built-in micro SD/SDHC/SDXC card slot,up to 128 GB</p>		<p>DS-2CD2163G0-IS</p>	<p>12</p>
<p>61,910,000</p>	<p>8 MP IR Fixed Dome Network Camera 1/2.5" Progressive Scan CMOS 3840 × 2160@15fps audio and alarm interface available 2.8/4/6/8mm fixed lens H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR BLC/3D DNR/ROI/HLC IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD2183G0-IS</p>	<p>13</p>




<p>33,920,000</p>	<p>2 MP 1/2.7" Progressive Scan CMOS 1920 × 1080@30fps IR: 10 m exir PIR: 10m H.265,H.265+ 120dB WDR Built-in Micro SD/SDHC/SDXC slot, up to 128 GB PoE Wi-Fi</p>		<p>DS-2CD2423G0IW</p>	<p>14</p>
<p>41,980,000</p>	<p>4 MP 1/2.7" Progressive Scan CMOS 2688 × 1520 @25fps IR: 10 m exir PIR: 10m H.265,H.265+ 120dB WDR Built-in Micro SD/SDHC/SDXC slot, up to 128 GB PoE Wi-Fi</p>		<p>DS-2CD2443G0IW</p>	<p>15</p>
<p>57,670,000</p>	<p>3 Mp 2048 x 1536@15fps 2.8 mm to 12 mm Varifocal Lens IR LEDs Up to 30 Meters DWDR, 3D DNR, and BLC IP66 Supports On-Board Storage Up to 128 GB</p>		<p>DS-2CD2632F-I</p>	<p>16</p>
<p>89,040,000</p>	<p>4 MP IR Vari-focal Bullet Network Camera 1/3" Progressive Scan CMOS 2688 × 1520@30fps 2.8 to 12 mm varifocal lens audio and alarm interface available H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI/HLC IP66, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD2643G0-IZS</p>	<p>17</p>
<p>105,780,000</p>	<p>5 MP Network Fisheye 2560 × 1920 @30fps H.265, H.265+, H.264+, H.264 Support 14 display modes FOV: horizontal FOV 180°, vertical FOV 180° Dual video streams DC12V & PoE (802.3af), Support on-board storage, up to 128 GB Up to 8m IR range -S: Audio/Alarm IO</p>		<p>DS-2CD2955FWD-IS</p>	<p>18</p>

<p>29,840,000</p>	<p>2.0 MP CMOS 1/4" Progressive Scan CMOS Support motorized Pan & Tilt Digital WDR IR range . 10 meters Support Wi-Fi, support WPS configuration Two-way audio Built-in microphone and speaker Support 128G on-board storage 5V DC</p>	<p>1.0</p> 	<p>DS-2CD2Q10FDIW</p>	<p>19</p>
<p>48,080,000</p>	<p>4 MP 1/3"Progressive Scan CMOS 2688 × 1520@30fps 2.8/4/6/8 mm fixed lens H.265+, H.265, H.264+ Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI/HLC IP67 IR Range: Up to 50 m Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD2T43G0-I5</p>	<p>20</p>
<p>58,510,000</p>	<p>6 MP 1/3"Progressive Scan CMOS 3840 × 2160 @ 15fps 2.8/4/6/8 mm fixed lens H.265+, H.265, H.264+ Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI/HLC IP67 IR Range: Up to 80 m Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD2T63G0-I8</p>	<p>21</p>
<p>69,540,000</p>	<p>8 MP 1/3"Progressive Scan CMOS 3840 × 2160 @ 15fps 2.8/4/6/8 mm fixed lens H.265+, H.265, H.264+ Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI/HLC IP67 IR Range: Up to 80 m Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>		<p>DS-2CD2T83G0-I8</p>	<p>22</p>
<p>23,320,000</p>	<p>2 MP Fixed Bullet Network Camera</p> <p>High quality imaging with 2 MP resolution</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging even with strong back lighting thanks to DWDR technology</p>		<p>DS-2CD1023G0E-I</p>	<p>23</p>





<p>49,190,000</p>	<p>Water- and dust- resistant (IP67)</p> <p>EXIR 2.0: advanced infrared technology with long IR range.</p> <p>2 MP Varifocal Bullet Network Camera</p> <p>High quality imaging with 2 MP resolution</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging even with strong back lighting thanks to DWDR technology</p> <p>Up to 128 GB SD card slot for storage</p> <p>2.8 to 12 mm motorized vari-focal lens for easy installation and monitoring</p> <p>dust and dust resistant (IP67), EXIR 2.0: advanced infrared technology with long IR range.</p>		<p>DS-2CD1623G0-I</p>	<p>24</p>
<p>49,190,000</p>	<p>1/2.8" progressive scan CMOS</p> <p>3D DNR (Digital Noise Reduction)</p> <p>1920 ×1080@30fps</p> <p>Up to 50 m IR range</p> <p>2.7mm to 13.5mm motorizedvari-focal lens</p> <p>PoE (Power over Ethernet)</p> <p>IP67, IK10</p> <p>H.265+, H.265, H.264+, H.264</p> <p>Triplestream 120 dBWDR (Wide Dynamic Range)</p>		<p>DS-2CD1723G0-I</p>	<p>25</p>



<p>41,420,000</p>	<p>Up to 5megapixel high resolution</p> <p>Electronic shutterλDual video streams</p> <p>DigitalWide Dynamic Range</p> <p>3D Digital Noise Reduction</p> <p>3-axis adjustment</p> <p>DC12V & PoE</p> <p>IR cut filter with auto switch</p> <p>Up to 30m IR range</p> <p>IP66weather-proof protection</p> <p>Mobile Monitoring via EZVIZ P2P or iVMS-4500</p> <p>4K Outdoor WDR Fixed Bullet Network Camera</p> <p>High quality imaging with 8 MP resolution</p>		<p>DS-2CD2052-I</p>	<p>26</p>
<p>56,820,000</p>	<p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light due to 120 dB true WDR technology</p> <p>Water and dust resistant (IP67)</p> <p>Robust structure design with full metal materials.</p>		<p>DS-2CD2083G0-I</p>	<p>27</p>
<p>43,600,000</p>	<p>Up to 5 MP Resolution</p> <p>Full 1080p @ 30 fps</p> <p>4 mm / 6 mm Fixed Lens Options</p> <p>H.264+, H.264, MJPEG</p> <p>120 dB Wide Dynamic Range</p> <p>3D Digital Noise Reduction</p> <p>3-axis adjustment</p> <p>Up to 100 ft (30 m) IR Range</p> <p>MicroSD card slot supports up to 128 GB</p> <p>Audio and Alarm Inputs and Outputs</p> <p>IP67 and IK10 Protection</p>		<p>DS-2CD2152F-IS</p>	<p>28</p>





<p>37,740,000</p>	<p>12 VDC and PoE (802.3af)</p> <p>Up to 2 megapixel high resolution</p> <p>Full HD1080p video</p> <p>Dual stream</p> <p>2.8mm/4mm/6mm fixed lens</p> <p>120dB Wide Dynamic Range</p> <p>3D Digital Noise Reduction</p> <p>Backlight Compensation</p> <p>Support on-board storage, up to 64GB</p> <p>DC12V & PoE</p> <p>Support H.264+</p> <p>High performance EXIR LED</p> <p>Up to 30m IR range</p> <p>IP67weather-proof protection</p> <p>3-axis adjustment</p>		<p>DS-2CD2322WD-I</p>	<p>29</p>
<p>46,560,000</p>	<p>4 megapixel high resolution</p> <p>Full HD 1080p real-time video</p> <p>2.8mm fixed lens, EXIR illuminator (up to 30m)</p> <p>Wide dynamic range, 3D DNR & BLC</p> <p>IP66, PoE</p>		<p>DS-2CD2342WD-I</p>	<p>30</p>
<p>31,380,000</p>	<p>Resolution: 2 MP (1920 x 1080)</p> <p>2.8 mm / 98.5° lens</p> <p>Mechanically switching IR filter</p> <p>H.264/MJPEG video compression</p> <p>IR range up to 10</p> <p>Connection via LAN or Wi-Fi</p> <p>Support for microSD/microSDHC/microSDXC cards up to 128 GB</p>		<p>DS-2CD2420F-IW</p>	<p>31</p>

<p>تماس حاصل نماييد</p>	<p>2MP PIR Cube Network Camera</p> <p>High quality imaging with 2 MP resolution</p> <p>Efficient H.265+ compression technology</p> <p>Provides real-time security via built-in two-way audio</p> <p>Detects human body through passive infrared is sensitive to body temperature (PIR)</p> <p>-W: Wi-Fi connection</p> <p>-D: DC power supply</p>		<p>DS-2CD2421G0-IW</p>	<p>32</p>
<p>58,730,000</p>	<p>4 mega pixel high resolution Full HD1080p real-time video 2.8mm Fixed Lens, Wide dynamic range 3D DNR & BLC, IP66. IR LEDs: up to 10m</p> <p>Compact design. Supports on board storage (up to 128GB)</p> <p>4 MP Outdoor WDR Fixed Mini Dome Network Camera</p> <p>High quality imaging with 4 MP resolution</p> <p>Efficient H.265+ compression technology</p>		<p>DS-2CD2542FWD-IS</p>	<p>33</p>
<p>57,650,000</p>	<p>Clear imaging against strong back light due to 120 dB true WDR technology</p> <p>Water and dust resistant (IP66) and vandal proof (IK08)</p> <p>-W: Wi-Fi connection</p> <p>-S: build-in microphone, audio and alarm interface available</p> <p>Mini size suitable for limited space</p>		<p>DS-2CD2543G0-IS</p>	<p>34</p>

<p>89,040,000</p>	<p>4 MP Outdoor WDR Motorized Varifocal Bullet Network Camera</p> <p>High quality imaging with 4 MP resolution</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light due to 120 dB true WDR technology</p> <p>-S: audio and alarm interface available</p> <p>Water and dust resistant (IP67)</p> <p>Motorized vari-focal lens for easy installation and monitoring</p> <p>Up to 2.0megapixel(1920 ×1080)high resolution</p> <p>Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB</p> <p>Great performance and long lifespanInfrared LED, Approx. 20to 30 meters IR range</p> <p>IR cut filter with auto switch</p> <p>DC12V & PoE</p> <p>The bit rate mode: CBR and VBR</p> <p>Wide Dynamic Range</p> <p>3D Digital Noise Reduction</p> <p>Backlight Compensation</p> <p>Auto Electronic Shutter</p> <p>Language: Portuguese, English and Chinese</p> <p>IP67weather-proof protection</p> <p>IK10vandal-proof protection</p> <p>Mobile Monitoring via Hik-Connector iVMS-4500</p>		<p>DS-2CD2643G1-IZS</p>	<p>35</p>
<p>42,800,000</p>	<p>4MP IR VFDome Network Camera</p> <p>BLC/3D DNR/ROI</p> <p>IP67, IK10</p> <p>Built-in micro SD/SDHC/SDXC card slot, upto 128 GB</p> <p>3-Axis adjustment</p> <p>1/3"Progressive Scan CMOS</p> <p>2560×1440@30fps□2.8to 12mm</p> <p>Varifocallens</p> <p>Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR</p> <p>H.265+, H.265, H.264+, H.264</p> <p>Three streams</p> <p>120dB WDR</p> <p>2 behavior analyses, and face detection</p>		<p>DS-2CD2720F-I</p>	<p>36</p>
<p>89,040,000</p>	<p>4MP IR VFDome Network Camera</p> <p>BLC/3D DNR/ROI</p> <p>IP67, IK10</p> <p>Built-in micro SD/SDHC/SDXC card slot, upto 128 GB</p> <p>3-Axis adjustment</p> <p>1/3"Progressive Scan CMOS</p> <p>2560×1440@30fps□2.8to 12mm</p> <p>Varifocallens</p> <p>Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR</p> <p>H.265+, H.265, H.264+, H.264</p> <p>Three streams</p> <p>120dB WDR</p> <p>2 behavior analyses, and face detection</p>		<p>DS-2CD2743G0-IZS</p>	<p>37</p>

<p>68,800,000</p> <p>تماس حاصل فرمایید</p>	<p>Up to 3 megapixel high resolution Max. 2048 × 1536 @30fps 2.8mm fixed lens Powered by Darkfighter H.265, H.265+, H.264+, H.264 120dB Wide Dynamic Range 3D Digital Noise Reduction 12 VDC & PoE (802.3af) IR range: 80m Support on-board storage, up to 128 GB IP67 BLC/3D DNR/ROI/HLC 6 MP Outdoor WDR Fixed Bullet Network Camera</p> <p>High quality imaging with 6 MP resolution</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light due to 120 dB true WDR technology</p> <p>Water and dust resistant (IP67)</p> <p>Robust structure design with full metal material 2 MP ColorVu Fixed Mini Bullet Camera</p> <p>2 MP full time color bullet camera</p> <p>24/7 full color imaging</p> <p>Warm supplemental light with 20 m range</p> <p>تماس حاصل فرمایید Clear imaging even against strong back lighting due to 130 dB true WDR technology</p> <p>3D DNR technology delivers clean and sharp images</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS);</p>	  	<p>DS-2CD2T35FWD-I8</p> <p>DS-2CD2T63G0-I5</p> <p>DS-2CE10DFT-F</p>	<p>38</p> <p>39</p> <p>40</p>
<p>20,760,000</p>	<p>2 MP Indoor Audio Fixed Cube Network Camera</p> <p>High quality imaging with 2 MP resolution</p>		<p>DS-2CV2U21FD-IW</p>	<p>41</p>







	<p>Efficient H.264 compression technology</p> <p>Clear imaging even with strong back lighting due to DWDR technology</p> <p>Up to 128 GB SD card slot for storage</p> <p>Provides real-time security via two-way audio</p> <p>Wi-Fi connection and easy installation</p>			
<p>148,810,000</p>	<p>4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome</p> <p>Accurate human and vehicle target classification and alarm based on deep learning algorithm</p> <p>Support face capture. Up to 5 faces captured at the same time</p> <p>1/2.8" Progressive Scan CMOS</p> <p>Up to 1920 × 1080@30fps resolution</p> <p>Min. illumination: Color: 0.005Lux @ (F1.6, AGC ON), B/W: 0.001Lux @ (F1.6, AGC ON), 0 Lux with IR</p> <p>25× optical zoom, 16× digital zoom</p> <p>WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus</p> <p>Up to 100m IR distance</p> <p>1/2.8" Progressive Scan CMOS</p> <p>Up to 2048 x 1536 Resolution</p>		<p>DS-2DE4225IW-DE</p>	<p>42</p>
<p>237,770,000</p>	<p>30× Optical Zoom, 16× Digital Zoom</p> <p>IR Distance up to 492 ft (150 m)</p> <p>Digital WDR</p> <p>3D Intelligent Positioning Function</p> <p>Support for H.265+/H.265 Video Compression IP66, IK10</p> <p>24 VAC/Hi-PoE (injector supplied), 32 W</p>		<p>DS-2DE5220IW-AE</p>	<p>43</p>





<p>155,130,000</p>	<p>1/2.8" Progressive Scan CMOS</p> <p>1080P Full HD resolution</p> <p>30X / 20X optical zoom, 16X digital zoom</p> <p>100m IR distance</p> <p>True Day/Night, 3D DNR, Digital WDR</p> <p>3D intelligent positioning</p> <p>Support 24V AC / High-PoE power supply</p> <p>Full HD 1080P real-time video</p> <p>32X optical zoom, 16X digital zoom</p> <p>4.8 - 153mm</p> <p>Up to 150m IR distance</p>		<p>DS-2DE7184-AE</p>	<p>44</p>
<p>273,510,000</p>	<p>IP66</p> <p>H.265+ compression</p> <p>3D intelligent positioning</p> <p>120dB WDR</p> <p>2 alarms in / 1 alarm out Audio input</p> <p>24V AC / Hi-PoE (40W) (802.3at)</p>		<p>DS-2DE7232IW-AE</p>	<p>45</p>
<p>284,320,000</p>	<p>1/2.8" Progressive Scan CMOS</p> <p>2048 × 1536@30fps Resolution</p> <p>20× optical zoom, 16× digital zoom</p> <p>WDR</p> <p>3D Positioning</p> <p>24VAC & Hi-PoE</p> <p>Up to 150m IR distance</p>		<p>DS-2DE7320IW-AE</p>	<p>46</p>
<p>139,430,000</p>	<p>3-ch panoramic images in different directions and 1-ch close-up image</p> <p>Support PTZ linkage</p> <p>1-ch audio input and 1-ch audio output</p> <p>Support H.265 video compression</p> <p>Up to 10 m IR (radius)</p>		<p>DS-2PT3326IZ-DE3</p>	<p>47</p>

36,240,000	8-Port 100Mbps Long-Range Unmanaged PoE Switch Max. port power 30 W		DS-3E0109P-E	48
81,070,000	IEEE 802.3at and IEEE 802.3af Power over Ethernet (PoE) compliant 16x10/100Mbps Auto-MDIX PoE ports Provides up to 30 watts per PoE port PoE power budget 230W4 KV surge protection for PoE ports IEEE 802.3x flow control support Plug-and-play installation 7.2 Gbps switching fabric bits RAM Data Buffer4K MAC address entries, Sturdy metal enclosure		DS-3E0318P-E	49
122,600,000	Up to 250m transmission achievable at reduced mbps rate IEEE 802.3at and IEEE 802.3af Power over Ethernet (PoE) compliant 24 x 10/100Mbps Auto-MDIX PoE ports 2 x 1GB uplink ports Provides up to 30 watts per PoE port PoE power budget 370W 4 kV surge protection for PoE ports		DS-3E0326P-E	50
13,910,000	IEEE 802.3at and IEEE 802.3af Power over Ethernet (PoE) compliant 4 x 10/100Mbps Auto-MDIX PoE ports Provides up to 30 watts per PoE port PoE power budget 58W 4 kV surge protection for PoE ports		DS-3E0105P-E	51
	لیست قیمت محصولات هایک ویژن مهر 1399	شرکت هوشمندافزار آسیا 5- 02634200921	NVR	
قیمت (ریال)	مشخصات فنی	تصویر	مدل کالا	ردیف
32,750,000	H.265+/H.265 compression Full channel recording at up to 4 MP resolution 4 POE port HDMI/VGA output at 1080p resolution 1-ch playback at 4 MP resolution or 2-ch at 1080p resolution 1 SATA HDD up to 6TB		DS-7104NIQ1/4P/M	52
19,830,000	H.265+/H.265 compression Full channel recording at up to 4 MP resolution HDMI/VGA output at 1080p resolution		DS-7104NIQ1/M	53
	1-ch playback at 4 MP resolution or 2-ch at 1080p resolution 1 SATA HDD up to 6TB			

<p>47,620,000</p>	<p>H.265+/H.265 compression Full channel recording at up to 4 MP resolution 8 POE port HDMI/VGA output at 1080p resolution 1-ch playback at 4 MP resolution or 2-ch at 1080p resolution 1 SATA HDD up to 6TB</p>		<p>DS-7108NIQ1/8P/M</p>	<p>54</p>
<p>24,920,000</p>	<p>H.265+/H.265 compression Full channel recording at up to 4 MP resolution HDMI/VGA output at 1080p resolution 1-ch playback at 4 MP resolution or 2-ch at 1080p resolution 1 SATA HDD up to 6TB capacity</p>		<p>DS-7108NIQ1/M</p>	<p>55</p>
<p>37,370,000</p>	<p>Dual-OS design ANR Input H.265/H.264/H.264+ video formats Up to 16 IPcameras can be connected Recording at up to 8 MP resolution Supports live view, storage, and playback of the connected camera at up to 8MP resolutionHD Output HDMI Videooutput at up to 4K (3840 x2160) resolutionHD Storage 1 HDD Up to 6TB</p>		<p>DS-7608NI-K1</p>	<p>56</p>
<p>36,870,000</p>	<p>H.265+/H.265/H.264/H.264+ video formats Up to 8 IPcameras can be connected Recording at up to 8 MP resolution HDMI Videooutput at up to 4K 1 SATA up to 6TB</p>		<p>DS-7608NI-Q1</p>	<p>57</p>
<p>44,480,000</p>	<p>H.265+/H.265/H.264/H.264+ video formats Up to 16 IPcameras can be connected Recording at up to 8 MP resolution HDMI Videooutput at up to 4K 1 SATA up to 6TB</p>		<p>DS-7616NI-Q1</p>	<p>58</p>
<p>46,540,000</p>	<p>H.265+/H.265/H.264/H.264+ video formats Up to 16 IPcameras can be connected Recording at up to 8 MP resolution HDMI Videooutput at up to 4K 2 SATA up to 6TB</p>		<p>DS-7616NI-Q2</p>	<p>59</p>
<p>94,800,000</p>	<p>H.265+/H.265/H.264/H.264+ video formats Up to 16 IPcameras can be connected Recording at up to 8 MP resolution HDMI Videooutput at up to 4K 2 SATA up to 6TB 16 port poe</p>		<p>DS-7616NIQ2/16P</p>	<p>60</p>
<p>98,030,000</p>	<p>H.265+/H.265/H.264/H.264+ video formats Up to 16-ch IPcameras Recording at up to 8 MP resolution HDMI Videooutput at up to 4K 4SATA up to 6 TB</p>		<p>DS-7716NI-Q4</p>	<p>61</p>

<p>146,890,000</p>	<p>Dual-OS design ANR technology H.265/H.265+/H.264/H.264+ Up to 32 IPCameras Recording at up to 8MP resolution HDMI Videooutput at up to 4K Up to 4 SATA 10 TB</p>		<p>DS-7732NI-K4</p>	<p>62</p>
<p>121,300,000</p>	<p>H.265+/H.265/H.264/H.264+video formats Up to 32-ch IP Recording at up to 8 MP resolution HDMI Videooutput at up to 4K 4SATA up to 10 TB</p>		<p>DS-7732NI-Q4</p>	<p>63</p>
<p>177,960,000</p>	<p>H.265+/H.265/H.264/H.264+video formats Up to 32-ch IP Recording at up to 8 MP resolution HDMI Videooutput at up to 4K 4SATA up to 10 TB 16 POE port</p>		<p>DS-7732NIQ4/16P</p>	<p>64</p>
<p>34,950,000</p>	<p>third-party network cameras supported Up to 8 Megapixels resolution recording HDMI output up to 3840x2160 resolution Can be connected up to 16 network cameras 160mbps incoming bandwidth 2 SATA interface up to 2 x 6TB maximum Plug & Play with up to 16 independent PoE network interfaces</p>		<p>DS-7604NI-K1</p>	<p>65</p>
<p>30,510,000</p>	<p>4-ch 1U 4K NVR Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 4K high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 40 Mbps high incoming bandwidth ensures IP cameras can be connected 4-ch 1U 4 PoE 4K NVR Up to 4 channel IP cameras can be connected</p>		<p>DS-7604NI-Q1</p>	<p>66</p>
<p>43,610,000</p>	<p>Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 4K high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 40 Mbps high incoming bandwidth ensures IP cameras can be connected</p>		<p>DS-7604NI-Q1/4P</p>	<p>67</p>

<p>38,010,000</p>	<p>third-party network cameras supported Up to 6 Megapixels resolution recording HDMI and VGA output at up to 1920×1080P resolution 4-ch network cameras can be connected with 40M/80M/160M incoming bandwidth. Plug & Play with up to 8 independent PoE network interfaces</p>		<p>DS-7608NI-E2</p>	<p>68</p>
<p>63,600,000</p>	<p>third-party network cameras supported Up to 6 Megapixels resolution recording HDMI and VGA output at up to 1920×1080P resolution 8-ch network cameras can be connected with 40M/80M/160M incoming bandwidth. Plug & Play with up to 8 independent PoE network interfaces</p>		<p>DS-7608NI-E2/8P</p>	<p>69</p>
<p>41,890,000</p>	<p>third-party network cameras supported Up to 6 Megapixels resolution recording HDMI and VGA output at up to 1920×1080P resolution 16-ch network cameras can be connected with 40M/80M/160M incoming bandwidth. Plug & Play with up to 8 independent PoE network interfaces</p>		<p>DS-7616NI-E2</p>	<p>70</p>
<p>66,700,000</p>	<p>third-party network cameras supported Up to 6 Megapixels resolution recording HDMI and VGA output at up to 1920×1080P resolution 16-ch network cameras can be connected with 40M/80M/160M incoming bandwidth. Plug & Play with up to 8 independent PoE network interfaces</p>		<p>DS-7616NI-E2/8P</p>	<p>71</p>
<p>88,960,000</p>	<p>third-party network cameras supported Up to 6 Megapixels resolution recording HDMI and VGA output at up to 1920×1080P resolution 16-ch network cameras can be connected with 40M/80M/160M incoming bandwidth. Plug & Play with up to 8 independent PoE network interfaces</p>		<p>DS-7616NI-E2/16P</p>	<p>72</p>
<p>50,420,000</p>	<p>16-ch 1U 4K NVR</p> <p>Up to 16 channel IP cameras can be connected</p> <p>Supports decoding H.265+/H.265/H.264+/H.264 video formats</p> <p>Up to 4K high-definition live view, storage and playback</p> <p>Up to 8-ch @ 1080p decoding capacity</p> <p>Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected</p>		<p>DS-7616NI-K2</p>	<p>73</p>

<p>116,610,000</p>	<p>16-ch 1.5U 4K NVR</p> <p>Up to 16 channel IP cameras can be connected</p> <p>Supports decoding H.265+/H.265/H.264+/H.264 video formats</p> <p>Up to 4K high-definition live view, storage and playback</p> <p>Up to 8-ch @ 1080p decoding capacity</p> <p>Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected</p> <p>16-ch 1.5U 4K NVR</p> <p>Up to 16 channel IP cameras can be connected</p> <p>Supports decoding H.265+/H.265/H.264+/H.264 video formats</p> <p>Up to 4K high-definition live view, storage and playback</p> <p>Up to 8-ch @ 1080p decoding capacity</p> <p>Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected</p>		<p>DS-7716NI-K4</p>	<p>74</p>
<p>160,290,000</p>	<p>16-ch 1.5U 4K NVR</p> <p>Up to 16 channel IP cameras can be connected</p> <p>Supports decoding H.265+/H.265/H.264+/H.264 video formats</p> <p>Up to 4K high-definition live view, storage and playback</p> <p>Up to 8-ch @ 1080p decoding capacity</p> <p>Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected</p>		<p>DS-7716NI-K4/16p</p>	<p>75</p>
<p>188,420,000</p>	<p>32-ch 1.5U 16 PoE 4K NVR</p> <p>Up to 32 channel IP cameras can be connected</p> <p>Supports decoding H.265+/H.265/H.264+/H.264 video formats</p> <p>Up to 4K high-definition live view, storage and playback</p> <p>Up to 8-ch @ 1080p decoding capacity</p> <p>Up to 256 Mbps high incoming bandwidth ensures IP cameras can be connected</p>		<p>DS-7732NI-K4/16P</p>	<p>76</p>
		<p>شركت هوشمندافزار آسيا 5- 02634200921</p>	<p>لوازم جانبی</p>	
<p>قیمت (ریال)</p>	<p>مشخصات فنی</p>	<p>تصویر</p>	<p>مدل کالا</p>	<p>ردیف</p>
<p>6,840,000</p>	<p>پایه براکت Indoor and outdoor جنس فلز آلومینیوم تقویت شده رنگ سفید</p>		<p>DS-1602ZJ</p>	<p>77</p>

7,490,000	Indoor and outdoor جنس فلز آلومینیوم تقویت شده رنگ سفید مجهز به طناب ایمنی و ضد آب		DS-1661ZJ	78
8,600,000	Indoor and outdoor جنس فلز آلومینیوم تقویت شده رنگ سفید مجهز به طناب ایمنی و ضد آب		DS-1662ZJ	79
2,500,000	پایه اسپیددام جنس فلز آلومینیوم تقویت شده رنگ سفید		DS-1681ZJ	80
46,940,000	کابل شبکه 6CAT با مترای 305 متر قطر هسته: 53.0 میلی متر عملکرد عالی در انتقال برق و دیتا کیفیت تأیید شده توسط آزمون Fluke تضمین فاصله انتقال PoE طولانی		DS-1LN6-UE-W	81
51,660,000	کابل شبکه 6CAT با قطر کامل 305 متر قطر هسته: 565.0 میلی متر عملکرد عالی انتقال برق و دیتا کیفیت تأیید شده توسط آزمون Fluke تضمین فاصله انتقال PoE طولانی		DS-1LN6-UU	82
138,420,000	TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs 7" TFT active matrix LCD monitor TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps		DS-TT-X41Ttester	83
346,900,000	کیبوردی شبکه		DS-1100KI	84
83,140,000	کیبورد PTZ		DS-1005KI	85